



# PSU90 /CH /2U/ 3U PSU105B POWER SUPPLY 24 VOLT AC 4A 100VA

A high specification compact wall mounted AC power supply, this is suitable for a wide range of applications in the fire and security industry, also available in chassis format or a 19" rack unit. The power supply unit is fitted with a three way fuse card to give independent outputs for three devices.

### **DIMENSIONS**

**PSU90** Supplied in white steel lift off lid enclosure (LV1), 200 X 105 X 90mm weight 2.5Kg.

**PSU90/CH** Chassis Only 180 x 135 bright aluminium plate weight 1.3Kg.

PSU90/2U/3U 19" Rack version also available weight 5 & 5.3Kg.

**PSU105B** A rugged IP56 rated enclosure with a lift off lid and a number of 20mm cable glands providing easy access into the enclosure. Enclosure size 240 X 190 X 90mm, with 5 x 20mm cable glands weight 3Kg.

### **CONSTRUCTION**

A rugged steel vented enclosure with a lift off lid and a number of 20mm conduit knockouts providing easy access into the enclosure, finished in powder coated white to match other office and industrial control systems.

The power supply is mounted easily to any flat surface utilising an external fixing flange that has two keyhole slots on each side for ease of fitting and removal if required. The front of the enclosure can also be screen printed with your company logo in one colour upon request for a small additional cost.

#### TECHNICAL SPECIFICATION

Mains Input Voltage 230/240 volts 50/60 Hz
Mains Input Fuse 2amp S/D Slow destroy fuse

Mains Currant Consumption  $0.64 \text{ amp } \{10 \text{ x} > \text{@ 1 msec inrush}\}$ 

Output Voltage 27.2 Volt AC

Output Fuse 3 x 1 amp ceramic fuse

Continuous Operating Current

Maximum Operating Current

4Amp

Mains Power Indication

YES

Heat Dissipation in Watt's for Air Con

Calculations. 67.2 W

## TRANSFORMER SPECIFICATION

Our Electrical Transformers are a high quality robust product, manufactured for us to the following standards. EN 60/742 TEC, BS3535 & UL1411.

VA Rating	100VA
Input Voltage	230Vac
Output Voltage	24Vac
Output Current	4A
Regulation Typ.	7%
Height x Diameter	47 x 90mm
Dimensions L x W x H	47 (H) x 90 (Dia) mm
Fixing Bolt Size	M6x60mm
Temperature Rise	+60°C
Weight	1kg

### **OPTIONS AVAILABLE**


### (Part no PSU/F??)

Fuse distribution cards of any number can also be specified upon request these will be mounted inside the steel enclosure on pillars. From 2 to 16 fuse outputs.

### (Part no TAMP)

Tamper switch this option is only available on boxed PSU's, this comes complete with wires (Black=common, Purple= normally closed, White= normally open)

19" rack mounted version also available.





LV Internals







75VA Chassis Version

## Warranty

All of our power supplies are manufactured with build quality and longevity in mind, we are constantly striving to improve upon an already reliable quality product with a very low failure rate, and because of our confidence in our end product's all our power supplies come with a two year return to base warranty against equipment failure.